



Model	WI-AC150
Hardware Features	V2
Hardware Features	
Interface	5*10/100/1000M Base-T Ethernet ports, supporting up to 4 WAN ports (Default: 1 WAN port,4 LAN ports)
Memory	RAM: 256MB Flash: 16MB
AP Unified Configuration	150APs
Recommended Bandwidth	Speed Up to 800Mbps
Power Supply	AC 100-240V 50/60Hz
Power Consumption(max)	25W
Software Features	
Network Access	PPPoE dial-up, DHCP client, static IP
Routing	Static routing, policy-based routing, carrier address routing,active/standby mode, load balancing based on source address, flow-based load balancing, port-based weighted load balancing of data streams
Security	ACL, DHCP static assignment, MAC address filtering dynamic ARP, static ARP binding, NAT, port mapping
Application Recognition	Support WAN Load Balancing Supports the ONVIF protocol Support 802.1Q VLAN TAG Support SD-LAN
Flow Contro	Support custom flow control polices, IP-based automatic bandwidth assignment
Traffic Audit	Real-time traffic audit, IP Traffic visualization
Authentication	Captive portal: One Key Auth, Pre-Shared Password Local User Auth, Voucher, Facebook, SMS Auth, RADIUS Auth Summary for Captive Portal
VPN	OpenVPN /PPTP/L2TP / IPsec
Behavior Management	Time-based and IP policy-based access control, website filtering
AP Management	Support Auto AP Discovery, RF optimization, Batch configuration, Overview View Multi-SSID configuration, SSID hiding, channel setting, Tx power setting, AP online upgrade STA blacklist and whitelist
Other Protocols	DHCP Server, DHCP Client, DHCP Option43/138, DNS Server, DDNS
Management	Support local management with web Support remote management with Wi-Tek Cloud platform
Others	
Product Dimensions (L x W x H)	440*220*45mm
Package Dimensions (L x W x H)	510*290*80mm
Product Weight	2.1kg
Package Weight	2.8kg
Environment	Operating Temperature: -20℃ ~ 55℃(-40℃ ~ 158℃) Storage Temperature: -40℃ ~ 70℃(-40℃ ~ 185℃) Operating Humidity: 5% ~ 95% (non-condensing) Storage Humidity: 5% ~ 95% (non-condensing)
Certification	CE, FCC, RoHS, UKCA, RCM