



Model	WI-CFS6012-L3
Hardware Features	
Interfaces	
Ports	12* 10Gbps SFP+ Slots
Management Port	1*Console port
Performance	
Memory and Flash	DRAM 512MB Flash 32MB
Switch Property	
Standards and Protocols	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.3ae, IEEE 802.3x, IEEE 802.1X, IEEE 802.1q, IEEE 802.1p, IEEE 802.1d, IEEE 802.1w, IEEE 802.3ad
Forwarding Mode	Store and Forward
Switching Capacity	240Gbps
Packet Packet Forwarding Rate	178.6Mpps
MAC Address Table	32k
Packet Buffer Memory	16MB
Jumbo Frame	12kB
Power Supply	
Input Power	100~240V AC, 50/60Hz, 2A Max
Power Consumption	11W
Physical Characteristics	
LED Indicators	PWR Indicator: On: the device power on is normal Off: the device is power off or failed Sys Indicator: Off:The system is being started or abnormal Blinking:The system is working normally Link Indicator: Off: No device is connected to the corresponding port. On: Indicates the link through that port is successfully established Blinking: Indicates that the Switch is actively sending or receiving data over that port. On green light: indicates 10G link On orange light: indicates 1000M/2.5G link
Button	Reset:Reset: Hold for >5 sec. to restore factory default.
Fan	2
Product Weight	2.38kg
Dimensions	330*230*44mm
Installation	Desktop, rack-mounted
Reliability	Surge Immunity: Common mode ±4KV Differential mode ±2KV ESD Protection: Contact discharge ±6KV Air discharge ±8KV
Operating Temperature	−10 ~ 50°C(14 ~ 122°F)
Storage Temperature	−40 ~ 70°C(−40 ~ 158°F)
Operating Humidity	10 ~ 90% RH non-condensing
Storage Humidity	10 ~ 90% RH non-condensing
Certification	
Certification	CE, FCC, RoHS, UKCA, RCM