



Model	WI-CGS5328-L3
Hardware Specifications	
Interfaces	
Combo Port	8*1000Mbps Combo Ports
SFP Slot	16*1000Mbps SFP Slots
SFP+ Slot	4* 10Gbps SFP+ Slots
Management Port	1*Console port
Performance	
Memory and Flash	DRAM: 512MB Flash: 32MB
Switch Property	
Standards and Protocols	IEEE802.3, IEEE802.3u, IEEE802.3ab, IEEE802.3z, IEEE802.3x, IEEE802.1x, IEEE802.1q , IEEE802.1p, IEEE802.1d, IEEE802.1w,IEEE802.3ad
Forwarding Mode	Store and Forward
Switching Capacity	128 Gbps
Packet Forwarding Rate	96 Mpps
MAC Address Table	16 k
Packet Buffer Memory	12 Mbit
Jumbo Frame	12 kB
Power Supply	
Input Power	AC 100–240V 50/60 Hz
Power Consumption	Idle: 115V 60Hz--36.2W 230V 50Hz--35.7W
Physical Characteristics	
LED Indicators	PWR Indicator: On: the device power on is normal Off: the device is power off or failed SYS Indicator: Off:The device is abnormal Blinking:The device is working normally LNK/ACT Indicator On: Port connected Off: Port disconnected Blinking: Data transmission.
Physical Characteristics	
Buttons	Reset:Hold for >5 sec. to restore factory default.
Fan Quantity	2
Dimensions (W*D*H)	440*260*44mm
Weight	Net Weight: 3.7 kg
	Package Weight: 4.38kg
Installation	Rack- Mounted
Environmental	
Reliability	Surge Immunity: Differential mode ±2KV Common mode ±4KV
	ESD Protection: Contact discharge ±6KV Air discharge ±8KV
Operating Temperature	−10℃-50℃(14°F-122°F)
Operating Humidity	−40℃-70 ℃(−40°F-158°F)
Storage Temperature	10-90% RH non-condensing
Storage Humidity	5-90% RH non-condensing
Certification	
Certification	CE, FCC, RoHS, UKCA, RCM