



Model	WI-CMS528F-L3	WI-CMS554F-L3
Hardware Specifications		
Interfaces		
Downlink Ports	24*10/100/1000Mbps RJ45 Ports	48*10/100/1000Mbps RJ45 Ports
Uplink Ports	4*10Gbps SFP+ Slots	6*10Gbps SFP+ Slots
Management Port	1 Console port	1 Console port
Performance		
Memory and Flash	DRAM 512MB Flash 32MB	
Switch Property		
Standards and Protocols	IEEE802.3, IEEE802.3u, IEEE802.3ab, IEEE802.3z, IEEE802.3x, IEEE802.1x, IEEE802.1q, IEEE802.1p, IEEE802.1d, IEEE802.1w, IEEE802.3ad, 802.3az	
Forwarding Mode	Store and Forward	
Switching Capacity	128 Gbps	216 Gbps
Packet Forwarding Rate	96 Mpps	161 Mpps
MAC Address Table	16 k	32 k
Packet Buffer Memory	12 Mbit	16 Mbit
Jumbo Frame	12 kB	
Power Supply		
Input Power	AC 100-240V, 50/60Hz	
Power Consumption	23.2W(Full load)	52.6W(Full load)
Physical Characteristics		
LED Indicators	PWR Indicator: Off: No power supply On: Indicates the switch has power Link Indicator: Off: No device is connected to the corresponding port On: Indicates the link through that port is successfully established Blinking: Indicates that the Switch is actively sending or receiving data over that port SYS Indicator: Blinking: The system is working properly Off: The system is being started or is abnormal SFP+ Indicator: Off: No device is connected to the corresponding port On: Indicates the link through that port is successfully established Blinking: Indicates that the Switch is actively sending or receiving data over that port	
Buttons	Reset: Hold for >5 sec. to restore factory default	
Fan Quantity	Fanless	1
Dimensions (W*D*H)	440*207*44mm	440*330*44mm
Weight	Net Weight: 2.75kg	Net Weight: 3.63kg
	Package Weight: 3.05kg	Package Weight: 3.9kg
Installation	Desktop, Rack-mounted	
Reliability	Surge Immunity: Differential mode ±2KV Common mode ±4KV	
	ESD Protection: Contact discharge ±6KV Air discharge ±8KV	
Operating Temperature	-10 - 50°C(14 -122°F)	
Storage Temperature	-40 - 70°C(-40 - 158°F)	
Operating Humidity	10 - 90% RH non-condensing	
Storage Humidity	10 - 90% RH non-condensing	
Certification		
Certification	CE, FCC, ROHS, UKCA, RCM	