



Model	WI-CMS6006F-L3	
Hardware Features		
Interfaces		
Interface	2*100M/1000M/2.5G/5G/10Gbps RJ45 Ports 4*1000M/2.5G/10Gbps SFP+ Slots	
Management Port	1*Console port	
Performance		
Memory and Flash	DRAM: 512MB Flash: 32MB	
Switch Property		
Standards and Protocols	IEEE802.3, IEEE802.1p, IEEE802.3u, IEEE802.1x, IEEE802.3ae, IEEE802.1s, IEEE802.1ab, IEEE802.1d, IEEE802.3z, IEEE802.1w, IEEE802.3x, IEEE802.3ad IEEE802.1q,	
Forwarding Mode	Store and Forward	
Switching Capacity	120Gbps	
Packet Forwarding Rate	89.28Mpps	
MAC Address Table	16k	
Packet Buffer Memory	12Mbit	
Jumbo Frame	12kB	
Power Supply		
Input Power	DC: 12V/3A	
Power Consumption	21W(Full Load)	
Physical Characteristics		
LED Indicators	PWR Indicator: Off: The device is power off or failed On: The device power on is normal SYS Indicator: Off: The system is being started or abnormal Blinking: The system is working normally Link Indicator: Off: No device is connected to the corresponding port Blinking: Indicates that the Switch is actively sending or receiving data over that port On green light: Indicates 10G link On orange light: Indicates 100/1000M/2.5G/5G link SFP+ Indicator: Off: No device is connected to the corresponding port Blinking: Indicates that the Switch is actively sending or receiving data over that port On green light: Indicates 10G link On orange light: Indicates 1000M/2.5G link	
Button	Reset: Hold for >5 sec. to restore factory default.	
Fan Quantity	1	
Fan Speed Control	Supported	
Dimensions (W*D*H)	220*130*38mm	
Weight	Net Weight: 0.92 kg	
	Package Weight: 1. 15 kg	
Installation	Desktop, Magnetic-mounted, Wall-mounted	
Reliability	Surge Immunity: Common mode ±6KV Differential mode ±1KV	
	ESD Protection: Contact discharge ±6KV Air discharge ±8KV	
Operating Temperature	-10~50°C(14~122°F)	
Storage Temperature	-40~70°C(-40~158°F)	
Operating Humidity	10~90% RH non-condensing	
Storage Humidity	10~90% RH non-condensing	
Certification		
Certification	CE, FCC, RoHS, UKCA, RCM	