



Products	WI-CPE111-KIT
Hardware Version	V3
Hardware Features	
Interface	1*10/100Mbps WAN (PoE IN) RJ45 port 1*10/100Mbps LAN RJ45 port
Frequency Range	2.401GHz ~ 2.483GHz (Channel 1~13) *Please follow national regulations to select the appropriate frequency.
Compliant Standards	IEEE 802.11b/g/n
Spatial Streams	2x2, MU-MIMO
Maximum Wireless Rate	300Mbps@2.4GHz
Antenna Gain	Build-in 8dBi directional antenna
Half Power Beamwidth (Typ.)	Horizontal: 65°, Vertical: 15°
Transmit Power	21±2dBm max. (adjustable)
Recommended Distance	2km
LED Indicator	1*PWR, Power indicator, 1*WAN port indicator, 1*LAN port indicator, 1*Wi-Fi indicator
DIP Switch	H: Base station mode, supports wireless point-to-point and point-to-multipoint long-distance transmission. C: CPE mode, a receiving point for connecting a wireless base station.
LED Display	Displays the current working mode and pairing group number.
Quick Pairing Function Button	“+” button: Press and hold the button for 3s to enable the pairing group adjustment function. When the LED Display starts to blink, press the button to raise the pairing group number. “-” button: When the LED Display starts to blink, press the button to reduce the pairing group number.
RST button	Long press over 5 seconds: Restore the factory default configuration.
Power Supply	PoE: 24V@0.5A (4/5+, 7/8-)
Power Consumption	<5W
Dimensions	180*88*59mm
Weight	0.25kg*2
Package Dimensions	260*190*100mm
Package Weight	1.03kg
Installation	Wall/Pole mounted
Material	Outdoor UV Stabilized Plastic
Reliability	
ESD Protection	Air discharge: ±8kV, Contact discharge: ±4kV
Lightning Protection	2kV
Operating Environment	-40°C to 70°C, 5%~95% (non-condensation)
Storage Environment	-40°C to 85°C, 5%~95% (non-condensation)
Ingress Protection	IP65
Software Features	
System Status	System information, Wireless information, Radio status, Flow Chart, Wireless Terminal Station
Operating Mode	Base Station, CPE Repeater, WISP Mode (Switch the paring mode to control by web)
WAN Configuration	Dynamic IP, Static IP
Wireless Configuration	Wireless enable/disable, Hide SSID Wireless Security: OPEN, WPA-TKIP, WPA2-AES, WPA/WPA2-Mixed, WPA-Enterprise, WPA2-Enterprise
Radion Parameter	WMM, Weak Signal Rejection Threshold, Wireless Channel, Tx Power Control Channel Bandwidth: Auto/20/40MHz
System Tools	Wi-Fi Connection Filter, Speed Test, Ping Watchdog, Scheduled Reboot, NTP, Ping, Traceroute
Management	Local WEB management, Remote Wi-Tek Cloud management