



Model	WI-FW5620-H
Operating Frequency	5.925-7.125GHz
Wireless Standards	WIFI 6E
Wireless Data Rate	2400Mbps
Channel Width	20/40/80/160 MHz
Max Throughput	1.7Gbps+
Proprietary Physical Layer	2x2MU-MIMO/OFDMA based on 802.11ax underlying technology
Networking interface	1*2.5Gigabit Ethernet + 1*Gigabit
Transmit Power Range	Max 29dBm @20MHz, Max 27dBm@40/80MHz, Max 26dBm@160MHz
Recommended Distance	20km
Antenna Frequency Range	4.9-7.125GHz
Antenna Gain	20dBi Dual Linear
Antenna Beam width	V:30°/ H30°
Power Supply	802.3at PoE In, or DC 12V
Power Consumption	<15W
Surge suppression	8KV
Weatherproof Enclosure	IP67
Antenna Size	Φ21*30 cm
Weight	2kg
Temperature	-30°C to 60°C
Working mode	AP WDS, Client WDS
Network Mode	Bridge/Router
Firewall	Port Forwarding , DMZ, ACL Filtering
Wireless Security	WPA-PSK, WPA2-PSK, WPA/WPA2-PSK, WPA2-PSK/WPA3-SAE, WPA3-SAE
VLAN	802.1Q with 802.1p priority
DHCP	DHCP Server, DHCP Client
Network Management	HTTP/HTTPS, SNMPv1/2, SNMPv3, TR069
QoS (Quality of Service)	Three-level priority (voice, high, low) with packet classification by DSCP, COS, VLAN ID, IP & MAC Address, broadcast, multicast, and station priority
ARQ	yes
Nominal Receive Sensitivity (w/FEC) @20 MHz Channel	MCS 0 = -95 dBm to MCS 11 (1024 QAM-5/6) = -64 dBm (per chain)
Nominal Receive Sensitivity (w/FEC) @40 MHz Channel	MCS 0 = -92 dBm to MCS 11 (1024 QAM-5/6) = -61 dBm (per chain)
Nominal Receive Sensitivity (w/FEC) @80 MHz Channel	MCS 0 = -89 dBm to MCS 11 (1024 QAM-5/6) = -58 dBm (per chain)
Nominal Receive Sensitivity (w/FEC) @160 MHz Channel	MCS 0 = -86 dBm to MCS 11 (1024 QAM-5/6) = -55 dBm (per chain)
Modulation Levels (Adaptive)	MCS 0 (BPSK) to MCS 11(1024 QAM-5/6)