



Model	WI-MC111GP
Interface	1*1000Mbps SFP Port 1*1000Mbps RJ-45 Port with 802.3af/at PoE Out
Wave Length	Depend on used SFP module
Transmission Media	Single-mode Fiber or Multi-mode Fiber
Transmission Distance	Depends on the inserting SFP module
Max Power Consumption	3W
Power Supply	DC-IN 48-52V/0.92A
Indicators	1000M(1000M Network Link) Solid on: 1000M Network Link 100M(100MNetwork data) 100M Network Link FX(Optical Link&Act) Solid on: Optical Link Connected Flash: Data Transmission Off: Optical Link Disconnected Link(Network Link&Act) Solid on: Link Connected Flash: Data Transmission Off: Link Disconnected PWR(Power indicator) Solid on: the device power on is normal Off: the device is power off or failed FDX(Network mode) Solid on: Full-Duplex Off: Half-Duplex
Dimensions	Product Dimension: 99*70*27mm Package Dimension: 207*161*55mm
Weight	Net Weight: 0.2kg Gross Weight: 0.45kg
Environment	OperatingTemperature:-20℃ ~ 50℃ (-4°F ~ 122°F) StorageTemperature:-40℃~70℃ (-40°F ~ 158°F) OperatingHumidity:10% ~ 90%(non-condensing) Storage Humidity: 5% ~ 95% (non-condensing)
Certi cation	CE, FCC, RoHS, UKCA, RCM