



Model		WI-PCMS310GF	WI-PCMS328GF
Hardware Version		V2	V2
Hardware Specifications			
Interfaces			
Downlink Ports		8 * 10/100/1000Mbps RJ45 Ports	24 * 10/100/1000Mbps RJ45 Ports
Uplink Ports		2 * 1000Mbps SFP Slots	2 * 1000Mbps Combo SFP ports 2 * 1000Mbps SFP Slots
Management port		1 * Console Por	1 * Console Port
PoE			
PoE Port		Port 1-8	Port 1-24
PoE Standard		802.3af/at	
PoE Power Supply Type		End-span	
PoE Pin Assignment		1/2(+), 3/6(-)	
PoE Power		30W Max. for each port, 140W Max. for PoE power budget	30W Max. for each port, 370W Max. for PoE power budget
Performance			
Memory and Flash		128MB DDR3, 32MB Flash	
Switch Property			
Standards and Protocols		IEEE 802.3i: 10BASE-T Ethernet IEEE 802.3u: 100BASE-X Fast Ethernet IEEE 802.3ab: 1000BASE-T Gigabit Ethernet IEEE 802.3z: 1000BASE-X Gigabit Ethernet(Optical fiber)	
Forwarding Mode		Store and Forward	
Switching Capacity		20 Gbps	56 Gbps
Packet Forwarding Rate		14.88 Mpps	41.66 Mpps
MAC Address Table		8 k	
Packet Buffer Memory		4.1 Mbit	4.1 Mbit
Jumbo Frame		10 kB	
Power Supply			
Input Power		AC100~240V 50/60 Hz	
Power Consumption		Idle: 14.2 W 100% Traffic Rate with PoE: 154.2 W	Idle: 27W 100% Traffic Rate with PoE: 397W
Physical Characteristics			
LED Indicators		PWR: On: The device power on is normal Off: The device is power off or failed SYS: Blinking: The Device system is operating normally Off: Device system or power connection abnormality PoE: On: Equipment connected, normal power supply Off: Port not for terminal equipment power supply Link: On: Port connected Blinking: Data transmission Off: Port disconnected	
Fan Quantity		N/A	2
Dimensions (W*D*H)		280*180*44mm	442*209*44mm
Weight		Net Weight: 1.72 kg	Net Weight: 2.55 kg
		Package Weight: 2.40 kg	Package Weight: 3.91 kg
Installation		Rack-Mounted、Desktop	
Button			
Reset		Hold for >5 sec. to restore factory default	
Environmental			
Reliability	Surge Immunity	IEC 61000-4-5 Common mode 4kV Differential mode 2kV	
	ESD Protection	IEC 61000-4-2 Contact discharge 6kV Air discharge 8kV	
Operating Temperature		-10℃ to 50℃(-14°F to 122°F)	
Operating Humidity		10% ~ 90% RH no condensation	
Storage Temperature		-40℃ to 70℃(-40°F to 158°F)	
Storage Humidity		5%~90% RH no condensation	
Certification			
Certification		CE, FCC, RoHS, UKCA, RCM	