



Model			WI-PE21E	WI-PE21G
Hardware Version			V1	V1
Hardware Specifications				
Interfaces				
Interfaces			PoE in port: 1 x 100Mbps PoE port with 802.3af/at 30W PoE output port: 1 x 100Mbps PoE port with 802.3af/at 30W 802.3af/at support auto MDI/MDI-X, auto-negotiation RJ-45Connecto	PoE in port: 1 x 1000Mbps PoE port with 802.3af/at 30W PoE output port: 1 x 1000MbpsPoE port with 802.3af/at 30W 802.3af/at support auto MDI/MDI-X, auto-negotiation RJ-45Connector
PoE				
PoE Port			2 10Mbps/100Mbps PoE ports	2 100Mbps/1000Mbps PoE ports
Power Supply				
Input Power			PoE DC 37-57V 0.65A Max	
Output Power			802.3af/at	
Physical Characteristics				
LED Indicators			pwr On: the device power on is normal Off: the device is power off or failed Link On: ports link up Off: ports link down Blinking: data on TX/RX	
Button			-	
Fan Quantity			Fanless	
Extender Dimension			112*40*25 mm	
Package Dimension			116*42*27 mm	
Weight			Net Weight: 0.065 kg	
			Package Weight: 0.07 kg	
Installation			Wall-Mounted, Desktop	
Environmental				
Reliability	Surge Immunity	IEC 61000-4-5 Common mode 3kV Differential mode 2kV		
	ESD Protection	IEC 61000-4-2 Contact discharge 6kV Air discharge 8kV		
Operating Temperature			0°C to 40°C(32°F to 104°F)	
Operating Humidity			5% ~ 90% RH no condensation	
Storage Temperature			-40°C to 75°C(-40°F to 185°F)	
Storage Humidity			5% ~ 95% RH no condensation	
Others				
Certification			CE, FCC, RoHS, UKCA, RCM	