



Model	WI-POE21E-O	WI-POE22E-O
Hardware Version	V2	V2
Hardware Specifications		
Interfaces	PoE in port: 1 x 1000Mbps PoE port with 802.3bt 60W PoE out port: 2 x 1000Mbps PoE port with 802.3af/at 30W support auto MDI/MDI-X, auto-negotiation RJ-45Connecto	PoE in port: 1 x 1000Mbps PoE port with 802.3bt 90W PoE out port: 1 x 1000Mbps PoE port with 802.3af/at 30W 1 x 1000Mbps PoE port with Hi-PoE 60W support auto MDI/MDI-X, auto-negotiation RJ-45Connector
Physical Characteristics		
LED Indicators	LAN(Green) Blinking: data and power are transmitting On: link established Off: no device connection	
Fan Quantity	Fanless	
Extender Dimension	150.5*72.93*43.8 mm	
Package Dimension	245*187*88 mm	
Weight	Net Weight: 0.34 kg	
	Package Weight: 0.70 kg	
Installation	Wall-Mounted, Desktop	
Environmental		
Reliability — Surge Immunity	IEC 61000-4-5 Common mode 4kV Differential mode 2kV	
Reliability — ESD Protection	IEC 61000-4-2 Contact discharge 6kV Air discharge 8kV	
Operating Temperature	-40℃ to 75℃(-40℉ to 167℉)	
Operating Humidity	10%~90% RH no condensation	
Storage Temperature	-40℃ to 80℃(-40℉ to 176℉)	
Storage Humidity	5%~90% RH no condensation	
Others		
Certification	CE, FCC, RoHS, UKCA, RCM	