



Model		WI-POE31-48V	WI-POE51-48V
Hardware Version		V1	V2
Hardware Specifications			
Interfaces			
Interfaces		1 10Mbps/100Mbps RJ45 LAN port 1 10Mbps/100Mbps PoE port	1 100Mbps/1000Mbps RJ45 LAN port 1 100Mbps/1000Mbps PoE port
PoE			
PoE Output Power		48V 0.5A Max	802. 3af/at
PoE Pin Assignment		1/2(+), 3/6(-)	
Power Supply			
Input Power		AC 100 ~ 240V 50/60Hz 0.3A Max	
Physical Characteristics			
LED Indicators		power Blinking: Abnormal power reception On: the device power on is normal Off: the device is power off or failed	
Fan Quantity		Fanless	
Injector Dimension		114*48*30 mm	
Package Dimension		200*132*42 mm	
Weight		Net Weight: 0.12 kg	
		Package Weight: 0.26 kg	
Installation		Desktop	
Environmental			
Reliability	Surge Immunity	IEC 61000-4-5 Common mode 3kV Differential mode 2kV	
	ESD Protection	IEC 61000-4-2 Contact discharge 6kV Air discharge 8kV	
Operating Temperature		-10℃ to 55℃(14°F to 131°F)	
Operating Humidity		5% ~ 90% RH no condensation	
Storage Temperature		-40℃ to 75℃(-40°F to 167°F)	
Storage Humidity		5%~95% RH no condensation	
Others			
Certification		CE, FCC, RoHS, UKCA, RCM	