



Model		WI-POE51S-48V
Hardware Version		V1
Hardware Specifications		
Interfaces		
Interfaces		1 * 10/100/1000Mbps PoE+ Input Port 1 * 10/100/1000Mbps Ethernet Port 1 * DC 12V 2A max. output plug
PoE		
PoE Standard		IEEE 802.3 af/at
PoE Pin Assignment		1/2(+),3/6(-);4/5(+),7/8(-)
Power Supply		
Input Power		802.3af/at 30W
Output Power		DC 12V 2A Max.
Physical Characteristics		
LED Indicators		PoE(Yellow) Solid on: PoE power received successfully Off: No PoE power supply access Blinking: Abnormal PoE power reception or abnormal DC output Data(Green) Solid on: Data connection is successful Blinking: Data transmission Off: No device connected
Switch Dimension (W*D*H)		95*26*20mm
Package Dimension		151*101mm
Weight	Net Weight: 0.05 kg	
	Package Weight: 0.05 kg	
Installation		Desktop
Environmental		
Reliability	Surge Immunity	IEC 61000-4-5 Differential mode ±800V
	ESD Protection	IEC 61000-4-2 Contact discharge ±6KV Air discharge ±8KV
Operating Temperature		0°C ~ 50°C(32°F to 122°F)
Operating Humidity		10% ~ 90% RH no condensation
Storage Temperature		-40°C ~ 70°C(-40°F to 158°F)
Storage Humidity		5% ~ 90% RH no condensation
Certification		
Certification		CE, FCC, RoHS, UKCA, RCM