



Model	WI-POE65-2.5G-30W	WI-POE65-2.5G-60W
Hardware Specifications		
Hardware Version	V1	V1
Interfaces		
Interfaces	1 100Mbps/1000Mbps/2.5Gbps Auto-Negotiation RJ45 LAN port 1 100Mbps/1000Mbps/2.5Gbps Auto-Negotiation RJ45 PoE port	
PoE		
PoE Port	1 100Mbps/1000Mbps/2.5Gbps Auto-Negotiation PoE port	1 100Mbps/1000Mbps/2.5Gbps Auto-Negotiation PoE port
PoE Standard	802.3 af/at	Hi-PoE 60W
PoE Power Supply Type	End-span	Mid-span and End-span
PoE Pin Assignment	1/2(+), 3/6(-)	1/2(+), 3/6(-) or 4/5(+), 7/8(-)
PoE Power Budget	30W Max	60W Max
Power Supply		
Input Power	AC 100-240V 50/60Hz	
Power Consumption	Idle: 2 W	Idle: 3 W
Physical Characteristics		
LED Indicators	**power** On: the device power on is normal Off: the device is power off or failed	
Fan Quantity	Fanless	
Injector Dimension	165*55*38 mm	185*92*41 mm
Package Dimension	195*160*55 mm	245*190*60 mm
Weight	Net Weight: 0.17 kg	Net Weight: 0.44 kg
	Package Weight: 0.41 kg	Package Weight:0.72 kg
Installation	Wall-Mounted，Desktop	
Environmental		
Reliability	Surge Immunity	IEC 61000-4-5 Common mode 6kV Differential mode 2kV
	ESD Protection	IEC 61000-4-2 Contact discharge 6kV
Reliability	ESD Protection	Air discharge 8kV
Operating Temperature	0℃ to 40℃(32℉ to 104℉)	
Operating Humidity	10% ~ 90% RH no condensation	
Storage Temperature	-40℃ to 75℃(-40℉ to 167℉)	
Storage Humidity	5% ~ 95% RH no condensation	
Others		
Certification	CE, FCC, RoHS, UKCA, RCM	