



Model		WI-POE90X	WI-POE60-24V
Hardware Version		V1	V1
Hardware Specifications			
Interfaces			
Interfaces		2 100/1000Mbps RJ45 Ports	
PoE			
PoE Port		1 port 1000M PoE IN(24V 45+ 78-) 1 port 1000M PoE OUT(802.3AF/AT)	1 port 1000M PoE IN(802.3AF/AT) 1 port 1000M PoE OUT(24V 45+ 78-)
PoE Standard		802.3 af/at compliant PoE	
PoE Power Supply Type		End-span	/
PoE Pin Assignment		1/2(+), 3/6(-)	4/5(+), 7/8(-)
PoE Power		24W Max	
Power Supply			
Input Power		DC IN 12-57V or PoE IN (24V 45+ 78-)	DC IN 48-55V or PoE IN (802.3AF/AT)
Power Consumption		Idle: 2 W	Idle: 2 W
Physical Characteristics			
LED Indicators		WI-POE90X PWR Blinking: Abnormal power reception On: The device is powered on Off: The device does not power PSE Blinking: 24V PoE Out abnormal On: 24V PoE Out is normal Off: No 24V PoE Out	
		WI-POE60-24V Speed Blinking: Abnormal power reception, or abnormal 24V output On: 48V PoE In/24V PoE Out Normal Off: No power, no 24V output Link Off: No device is connected to the corresponding port On: Indicates the link through that port is successfully established Blink: Data transfer	
Physical Characteristics			
Fan Quantity		Fanless	
Dimensions (W*D*H)		96×86×30 mm	111×40×25 mm
Weight		Net Weight: 0.15 kg	Net Weight: 0.065 kg
		Package Weight: 0.19 kg	Package Weight: 0.070 kg
Installation		Wall-Mounted、Desktop	
Environmental			
Reliability	Surge Immunity	IEC 61000-4-5 Common mode 6kV Differential mode 2kV	
	ESD Protection	IEC 61000-4-2 Contact discharge 6kV Air discharge 8kV	
Operating Temperature		-10°C to 70°C	10°C to 55°C
Operating Humidity		10%~90% RH no condensation	
Storage Temperature		-40°C to 70°C	
Storage Humidity		5%~90% RH no condensation	
Others			
Certification		CE, FCC, RoHS, UKCA, RCM	
Network Media		10BASE-T: UTP category 3, 4, 5 cable (Max 100m)EIA/TIA-568 100Ω STP (Max 100m) 100BASE-TX: UTP category 5, 5e cable (Max 100m)EIA/TIA-568 100Ω STP (Max 100m) 1000BASE-T: UTP category 5, 5e, 6 cable (Max 100m)	