



|                           |                                                                                                                                                                                                                                                                                         |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Model                     | WK-S205                                                                                                                                                                                                                                                                                 |
| Interfaces                |                                                                                                                                                                                                                                                                                         |
| Downlink Ports            | 5*10/100Mbps<br>RJ45 Ports                                                                                                                                                                                                                                                              |
| Switch Property           |                                                                                                                                                                                                                                                                                         |
| Standards and Protocols   | IEEE 802.3i   IEEE 802.3u   IEEE802.3x   IEEE802.3az                                                                                                                                                                                                                                    |
| Forwarding Mode           | Store and Forward                                                                                                                                                                                                                                                                       |
| Switching Capacity        | 1Gbps                                                                                                                                                                                                                                                                                   |
| Packet Forwarding Rate    | 745Kpps                                                                                                                                                                                                                                                                                 |
| MAC Address Table         | 1k                                                                                                                                                                                                                                                                                      |
| Packet Buffer Memory      | 448Kbit                                                                                                                                                                                                                                                                                 |
| Jumbo Frame               | 1536Bytes                                                                                                                                                                                                                                                                               |
| Input Power               | DC 5V 0.55A IN                                                                                                                                                                                                                                                                          |
| Physical Characteristics  |                                                                                                                                                                                                                                                                                         |
| LED Indicators            | PWR<br>Solid on: The power supply is normal<br>Off: The system power supply is abnormal<br>Link indicator<br>Solid on: A link has been established on the interface<br>Blinking: Data is being transmitted or received on the interface<br>Off: No link is established on the interface |
| Fan Quantity              | Fanless                                                                                                                                                                                                                                                                                 |
| Switch Dimensions (W*D*H) | 82*50*20mm                                                                                                                                                                                                                                                                              |
| Package Dimensions        | 85*85*83mm                                                                                                                                                                                                                                                                              |
| Weight                    | Net Weight: 0.040kg                                                                                                                                                                                                                                                                     |
|                           | Package Weight: 0.15kg                                                                                                                                                                                                                                                                  |
| Installation              | Desktop, Wall-mount                                                                                                                                                                                                                                                                     |
| Environmental             |                                                                                                                                                                                                                                                                                         |
| Surge Immunity            | 1kV                                                                                                                                                                                                                                                                                     |
| Air discharge             | 8kV                                                                                                                                                                                                                                                                                     |
| Operating environment     | -10℃ to 50℃(14°F to 122°F); 10%~90% RH no condensation                                                                                                                                                                                                                                  |
| Storage environment       | -40℃ to 70℃(-40°F to 158°F); 5%~90% RH no condensation                                                                                                                                                                                                                                  |
| Others                    |                                                                                                                                                                                                                                                                                         |
| Certification             | CE, FCC, RoHS, UKCA, RCM                                                                                                                                                                                                                                                                |