



Model	WK-S208
Interfaces	
Downlink Ports	8*10/100Mbps RJ45 Ports
Switch Property	
Standards and Protocols	IEEE 802.3i IEEE 802.3u IEEE802.3x IEEE802.3az
Forwarding Mode	Store and Forward
Switching Capacity	1.6Gbps
Packet Forwarding Rate	1.19Mpps
MAC Address Table	1k
Packet Buffer Memory	448Kbit
Jumbo Frame	1536Bytes
Input Power	DC 5V 0.55A IN
Physical Characteristics	
LED Indicators	PWR Solid on: The power supply is normal Off: The system power supply is abnormal Link indicator Solid on: A link has been established on the interface Blinking: Data is being transmitted or received on the interface Off: No link is established on the interface
Fan Quantity	Fanless
Switch Dimensions (W*D*H)	127*67*20mm
Package Dimensions	130*85*83mm
Weight	Net Weight: 0.088kg
	Package Weight: 0.20kg
Installation	Desktop, Wall-mount
Environmental	
Surge Immunity	1kV
Air discharge	8kV
Operating environment	-10℃ to 50℃(14°F to 122°F); 10%~90% RH no condensation
Storage environment	−40℃ to 70℃(−40°F to 158°F); 5%~90% RH no condensation
Others	
Certification	CE, FCC, RoHS, UKCA, RCM