



Model	WK-S305
Interfaces	
Downlink Ports	5*10/100/1000Mbps RJ45 Ports
Switch Property	
Standards and Protocols	IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE 802. 3x, IEEE 802. 3az
Forwarding Mode	Store and Forward
Switching Capacity	10Gbps
Packet Forwarding Rate	7.44Mpps
MAC Address Table	2k
Packet Buffer Memory	3Mb
Jumbo Frame	15KB
Input Power	DC 5V 0.55A IN
Physical Characteristics	
LED Indicators	PWR Solid on: The power supply is normal Off: The system power supply is abnormal Link indicator Solid on: A link has been established on the interface Blinking: Data is being transmitted or received on the interface Off: No link is established on the interface
Fan Quantity	Fanless
Switch Dimensions (W*D*H)	82*50*20mm
Package Dimensions	85*85*83mm
Weight	Net Weight: 0.040kg
	Package Weight: 0.15kg
Installation	Desktop, Wall-mount
Environmental	
Surge Immunity	1kV
Air discharge	8kV
Operating environment	-10℃ to 50℃(14°F to 122°F); 10%~90% RH no condensation
Storage environment	−40℃ to 70℃(−40°F to 158°F); 5%~90% RH no condensation
Others	
Certification	CE, FCC, RoHS, UKCA, RCM